




# Changzhou Tensun Bearing Co., Ltd.

## NTN 22330UAVS2 Bearing



Bearing No. 22330UAVS2

22330UAVS2 Bearing 2D drawings and 3D CAD models

Size	150x320x108 mm
Bore Diameter	150,000 mm
Outer Diameter	320,000 mm
Width	108,000 mm
d	150,000 mm
D	320,000 mm
H	108,000 mm
Category	Spherical Roller Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	43.55
EAN	4547359520217
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Shaft Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Straight
Cage Material	Bronze
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	Not Applicable
Withdrawal Nut	Not Applicable
Inch - Metric	Metric
Long Description	150MM Straight Bore; 320MM Outside Diameter;



## Changzhou Tensun Bearing Co., Ltd.

	108MM Width; C0-Medium Clearance; Shaft Mount; Double Row of Spherical Roller Bearings; Bronze Cage Material; Open Enclosure; Relubricatable
Category	Spherical Roller Bearing
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Weight / LBS	95.914
Outside Diameter	12.598 Inch   320 Millimeter
Width	4.252 Inch   108 Millimeter
Bore	5.906 Inch   150 Millimeter
Adapter Part Number	Not Applicable Inch   Not Applicable Millimeter
bore diameter:	150 mm
operating temperature range:	-40 to 120 ° C
outside diameter:	320 mm
cage material:	Brass
overall width:	108 mm
bearing material:	Through Hardened Steel
bore type:	Straight
cage type:	Machined
outer ring type:	Not Split
precision rating:	Not Rated
internal clearance:	Upper 2/3 of C4 range
finish/coating:	Uncoated
closure type:	Open
outer ring width:	108 mm



## Changzhou Tensun Bearing Co., Ltd.

lubrication hole type:	Lubrication Groove & Hole
inner ring width:	108 mm
dynamic load capacity:	1240000 N
fillet radius:	4 mm
static load capacity:	1320000 N
series:	223
maximum rpm:	1300 rpm
manufacturer product page:	<a href="#">Click here</a>